

## ELECTRONIC BACK-EYE, TV

### Back-TV and supervice - Platex PC670B

Screen: 7" TFT LCD  
Settings: OSD  
Video system: CCIR, PAL, NTSC  
Video signal: 1,0 Vp-p (75 Ohm)  
Power supply: 12v/24v DC  
Connectors: AMP, DIN, etc.  
Effektförbrukning: 0,007 A power from battery  
0,022 A Stand by  
0,047 A Back-TV/Side camera

Operating temperature: -20 till +60 degree C  
Storage temperature: -40 till +85 degree C  
Weight: 500 g  
Dimensions (WxHxD): 215x110x35 mm

Camera: CCD-type  
Housing: All-weather-type, metal  
Lens: Wide angle max  
Voltage: 12 V DC från monitorn  
Weight: 300 g  
Dimensions (WxHxD): 93x56x54 mm



- AV1, AV2 for extra equipment
- 12 v power out for extra equipment.
- Image can be switched to mirrored or normal image seperately for each camera.
- Prepared for two-camera-system
- Automatic Back-TV with reverse gear.
- Med hjälp av bildväxlare kan du få 5 st kameror.
- User manual, remote control and necessary brackets included.
- Camera cable 15 m with DIN connector.
- Other lengths on Special cable PC88 with AMP connectors for better resistance against water and salt etc. on request.